


- ▼ Capable of 1.8V Gate Drive
- ▼ Lower Gate Charge
- ▼ Surface Mount Package
- ▼ RoHS Compliant & Halogen-Free




N-CH	$BV_{DSS}$	16V
	$R_{DS(ON)}$	58m $\Omega$
	$I_D$	3.5A
P-CH	$BV_{DSS}$	-16V
	$R_{DS(ON)}$	125m $\Omega$
	$I_D$	-2.5A

## Description

XP2531 series are innovated design and silicon process technology to achieve the lowest possible on-resistance and fast switching performance. It provides the designer with an extreme efficient device for use in a wide range of power applications.

The SOT-26 package is widely used for all commercial-industrial applications.



## Absolute Maximum Ratings @ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Rating		Units
		N-channel	P-channel	
$V_{DS}$	Drain-Source Voltage	16	-16	V
$V_{GS}$	Gate-Source Voltage	+8	+8	V
$I_D@T_A=25^\circ\text{C}$	Drain Current <sup>3</sup> , $V_{GS}$ @ 4.5V	3.5	-2.5	A
$I_D@T_A=70^\circ\text{C}$	Drain Current <sup>3</sup> , $V_{GS}$ @ 4.5V	2.8	-2	A
$I_{DM}$	Pulsed Drain Current <sup>1</sup>	10	-10	A
$P_D@T_A=25^\circ\text{C}$	Total Power Dissipation	1.14		W
$T_{STG}$	Storage Temperature Range	-55 to 150		$^\circ\text{C}$
$T_J$	Operating Junction Temperature Range	-55 to 150		$^\circ\text{C}$

## Thermal Data

Symbol	Parameter	Value	Unit
Rthj-a	Maximum Thermal Resistance, Junction-ambient <sup>3</sup>	110	$^\circ\text{C}/\text{W}$

**N-CH Electrical Characteristics @ $T_j=25^{\circ}\text{C}$  (unless otherwise specified)**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	16	-	-	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance <sup>2</sup>	$V_{GS}=4.5V, I_D=3A$	-	-	58	m $\Omega$
		$V_{GS}=2.5V, I_D=2A$	-	-	70	m $\Omega$
		$V_{GS}=1.8V, I_D=1A$	-	-	85	m $\Omega$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	0.2	-	1	V
$g_{fs}$	Forward Transconductance	$V_{DS}=5V, I_D=3A$	-	9	-	S
$I_{DSS}$	Drain-Source Leakage Current	$V_{DS}=16V, V_{GS}=0V$	-	-	10	$\mu A$
$I_{GSS}$	Gate-Source Leakage	$V_{GS}=+8V, V_{DS}=0V$	-	-	+100	nA
$Q_g$	Total Gate Charge <sup>2</sup>	$I_D=3A$	-	7	12	nC
$Q_{gs}$	Gate-Source Charge	$V_{DS}=10V$	-	0.6	-	nC
$Q_{gd}$	Gate-Drain ("Miller") Charge	$V_{GS}=4.5V$	-	2	-	nC
$t_{d(on)}$	Turn-on Delay Time <sup>2</sup>	$V_{DS}=10V$	-	6	-	ns
$t_r$	Rise Time	$I_D=1A$	-	11	-	ns
$t_{d(off)}$	Turn-off Delay Time	$R_G=3.3\Omega$	-	17	-	ns
$t_f$	Fall Time	$V_{GS}=5V$	-	3	-	ns
$C_{iss}$	Input Capacitance	$V_{GS}=0V$	-	365	585	pF
$C_{oss}$	Output Capacitance	$V_{DS}=10V$	-	70	-	pF
$C_{rss}$	Reverse Transfer Capacitance	$f=1.0\text{MHz}$	-	60	-	pF
$R_g$	Gate Resistance	$f=1.0\text{MHz}$	-	1.5	3	$\Omega$

**Source-Drain Diode**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{SD}$	Forward On Voltage <sup>2</sup>	$I_S=0.9A, V_{GS}=0V$	-	-	1.3	V

**P-CH Electrical Characteristics @T<sub>j</sub>=25°C(unless otherwise specified)**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =-250uA	-16	-	-	V
R <sub>DS(ON)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-2A	-	-	125	mΩ
		V <sub>GS</sub> =-2.5V, I <sub>D</sub> =-1.6A	-	-	165	mΩ
		V <sub>GS</sub> =-1.8V, I <sub>D</sub> =-1A	-	-	210	mΩ
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =-250uA	-0.2	-	-1	V
g <sub>fs</sub>	Forward Transconductance	V <sub>DS</sub> =-5V, I <sub>D</sub> =-2A	-	5	-	S
I <sub>DSS</sub>	Drain-Source Leakage Current	V <sub>DS</sub> =-16V, V <sub>GS</sub> =0V	-	-	-10	uA
I <sub>GSS</sub>	Gate-Source Leakage	V <sub>GS</sub> =±8V, V <sub>DS</sub> =0V	-	-	±100	nA
Q <sub>g</sub>	Total Gate Charge <sup>2</sup>	I <sub>D</sub> =-2A V <sub>DS</sub> =-10V V <sub>GS</sub> =-4.5V V <sub>DS</sub> =-10V I <sub>D</sub> =-1A R <sub>G</sub> =3.3Ω V <sub>GS</sub> =-5V	-	6	10	nC
Q <sub>gs</sub>	Gate-Source Charge		-	0.8	-	nC
Q <sub>gd</sub>	Gate-Drain ("Miller") Charge		-	2	-	nC
t <sub>d(on)</sub>	Turn-on Delay Time <sup>2</sup>		-	7	-	ns
t <sub>r</sub>	Rise Time		-	20	-	ns
t <sub>d(off)</sub>	Turn-off Delay Time	-	23	-	ns	
t <sub>f</sub>	Fall Time	-	24	-	ns	
C <sub>iss</sub>	Input Capacitance	V <sub>GS</sub> =0V	-	380	610	pF
C <sub>oss</sub>	Output Capacitance	V <sub>DS</sub> =-10V	-	90	-	pF
C <sub>riss</sub>	Reverse Transfer Capacitance	f=1.0MHz	-	75	-	pF
R <sub>g</sub>	Gate Resistance	f=1.0MHz	-	8	16	Ω

**Source-Drain Diode**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V <sub>SD</sub>	Forward On Voltage <sup>2</sup>	I <sub>S</sub> =-0.9A, V <sub>GS</sub> =0V	-	-	-1.3	V

**Notes:**

- 1.Pulse width limited by Max. junction temperature.
- 2.Pulse test
- 3.Surface mounted on 1 in<sup>2</sup> copper pad of FR4 board, t<sub>sec</sub>≤5sec ; 180°C/W when mounted on min. copper pad.


THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.


XSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

XSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.


**N-Channel**




**Fig 1. Typical Output Characteristics**




**Fig 2. Typical Output Characteristics**




**Fig 3. On-Resistance v.s. Gate Voltage**



**Fig 4. Normalized On-Resistance v.s. Junction Temperature**




**Fig 5. Forward Characteristic of Reverse Diode**




**Fig 6. Gate Threshold Voltage v.s. Junction Temperature**


**N-Channel**




**Fig 7. Gate Charge Characteristics**




**Fig 8. Typical Capacitance Characteristics**




**Fig 9. Maximum Safe Operating Area**



**Fig 10. Effective Transient Thermal Impedance**




**Fig 11. Transfer Characteristics**




**Fig 12. Gate Charge Waveform**


**P-Channel**




**Fig 1. Typical Output Characteristics**




**Fig 2. Typical Output Characteristics**




**Fig 3. On-Resistance v.s. Gate Voltage**



**Fig 4. Normalized On-Resistance v.s. Junction Temperature**




**Fig 5. Forward Characteristic of Reverse Diode**




**Fig 6. Gate Threshold Voltage v.s. Junction Temperature**


**P-Channel**




**Fig 7. Gate Charge Characteristics**




**Fig 8. Typical Capacitance Characteristics**




**Fig 9. Maximum Safe Operating Area**



**Fig 10. Effective Transient Thermal Impedance**




**Fig 11. Transfer Characteristics**



**Fig 12. Gate Charge Waveform**

---

**MARKING INFORMATION**



Part Number : YA

Date Code : SS

SS:2004,2008,2012,2016,2020,2024...


SS:2003,2007,2011,2015,2019,2023...

SS:2002,2006,2010,2014,2018,2022...



SS:2001,2005,2009,2013,2017,2021...



**Package Outline : SOT-26**



SYMBOLS	Millimeters		
	MIN	NOM	MAX
A	2.70	2.90	3.10
B	2.60	2.80	3.00
C	1.40	1.60	1.80
D	0.30	0.40	0.50
E	0.00	0.05	0.10
H	1.00	1.15	1.30
G	—	1.95 (ref.)	—
I	0.10	0.15	0.20
J	0.30	0.45	0.60
L	—	0.95 (ref.)	—



- 1.All Dimension Are In Millimeters.
- 2.Dimension Does Not Include Mold Protrusions.

**SOT-26 FOOTPRINT :**

